



Kernel based pattern analysis methods using eigen-decompositions for reading Icelandic sagas

Christiansen, Asger Nyman; Carstensen, Jens Michael

Publication date:
2011

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Christiansen, A. N., & Carstensen, J. M. (2011). *Kernel based pattern analysis methods using eigen-decompositions for reading Icelandic sagas*. Poster session presented at Visionday 2010: Industrial, Kgs. Lyngby, Denmark. <http://www.visiondays.dk/>

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Kernel based pattern analysis methods using eigen-decompositions for reading Icelandic sagas

Asger Nyman Christiansen
Technical University of Denmark

We want to test the applicability of kernel based eigen-decomposition methods, compared to the traditional eigen-decomposition methods. We have implemented and tested three kernel based methods methods, namely PCA, MAF and MNF, all using a Gaussian kernel. We tested the methods on a multispectral image of a page in the book 'hauksbok', which contains Icelandic sagas.



The book 'hauksbok', which is written around the 14th century. Part of the book is unreadable because of large stains.



The sagas are scanned using VideometerLab, which produces multispectral images.

Principal components analysis

Maximum auto-correlation factors analysis




Minimum noise fraction factors analysis

The stain on the page makes it difficult to read the text no matter the method. A simple solution to this is to remove the stain beforehand by subtracting an average filtered image. An example of this is seen on the right.

Conclusion

We think the kernel based MNF produced the best result, especially because you can set the width of the Gaussian kernel to fit with what you want to find (in this case the letters). Furthermore the MNF removes the big stain when you set the size of the filter large enough. One big disadvantage of kernel based methods is the time and space consumption compared to the ordinary methods.

Traditional eigen-decomposition methods



Kernel based eigen-decomposition methods

